



Declaration of Performance

Nr. 14315-2990-02-CPR-15

1	Unique identification code of the product type	Baymer® Spray PP 2990 – Desmodur® 44V20L <i>Designation code: PU EN 14315-1-CT4(20)-GT8(20)-TFT10(20)-FRC9(20)-CCC1-W1,55-MU4,45</i>
2	Intended use/es	Thermal insulating products for buildings – Insitu formed sprayed rigid polyurethane (PUR) and polyisocyanurate (PIR) foam products
3	Manufacturer	Covestro BV Korte Groningerweg 1a 9607 PS Foxhol Nederland
4	Authorised representative	Not relevant
5	System/s of AVCP	System 4 for reaction to fire System 3 for the rest of essential characteristics
6a	Harmonised standard	EN 14315-1:2013
	Notified body/ies	Wetenschappelijk en technisch centrum voor het bouwbedrijf (WTCB) Lombardstraat 42 1000 BRUSSEL België Notified Body nummer : 1136
6b	European Assessment Document European Technical Assessment Technical Assessment Body Notified body/ies	Not relevant



Declaration of Performance

Nr. 14315-2990-02-CPR-15

7 Declared performance/s **See table 1**

Essential characteristics	Performance	Specifications
Reaction to fire	F	EN 13501-1
Water permeability	1,55 kg/m ² <i>Short term water absorption by partial immersion</i>	EN 1609 Method B
Thermal resistance	See performance chart	EN 14315-1:2013
Water vapour permeability	4,45 <i>μ value</i>	EN 12086 method A
Compressive strength	NPD	EN 826:2013
Durability of reaction to fire against ageing/degradation	Reaction to fire does not decrease with time	EN 14315-1:2013
Durability of thermal resistance against ageing/degradation	See performance chart	EN 14315-1:2013
Durability of compressive strength against ageing/degradation	NPD	EN 14315-1:2013
Continuous glowing combustion	No harmonized test method available	EN 14315-1:2013

Table 1

8 Appropriate Technical Documentation and/or Specific Technical Documentation **See table 2**

Specific characteristics	Performance	Specifications
French VOC Regulation French CMR components	A+ Pass	DEVL1101903D and DEVL1104875A; march and April 2011
AgBB	Pass	AgBB feb-15, DIBt oct-10
Belgian Regulation	Pass	C-2014/24239, may-15
Indoor Air Comfort®	Pass	5.3a, march-15
EN 717-1 ^s	E1	2004
BREEAM International	Compliant	GN22

Table 2



Declaration of Performance

Nr. 14315-2990-02-CPR-15

Performance chart

Type of facing: None or diffusion open		
Thickness	Declared aged thermal conductivity (λ_D)	Thermal resistance level (RD)
mm	W/m·K	m ² ·K/W
30	0,037	0,80
35	0,037	0,95
40	0,037	1,10
45	0,037	1,20
50	0,037	1,35
55	0,037	1,50
60	0,037	1,60
65	0,037	1,75
70	0,037	1,90
75	0,037	2,05
80	0,037	2,15
85	0,037	2,30
90	0,037	2,45
95	0,037	2,55
100	0,037	2,70
105	0,037	2,85
110	0,037	2,95
115	0,037	3,10
120	0,037	3,25
125	0,037	3,40
130	0,037	3,50
135	0,037	3,65
140	0,037	3,80
145	0,037	3,90
150	0,037	4,05
155	0,037	4,20
160	0,037	4,30
165	0,037	4,45
170	0,037	4,60
175	0,037	4,75
180	0,037	4,85
185	0,037	5,00
190	0,037	5,15
195	0,037	5,25
200	0,037	5,40

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above

Signed for and on behalf of the manufacturer by:

Name and function

Place and date of issue

Signature

Alix Uitham
Marketing & Sales manager

Foxhol
23-05-2016

Ceren Özdilek
R&D manager

Foxhol
23-05-2016